

DMA

TOOL BOX

PROFESYONEL TAŐIMA ANTALARI

PROFESSIONAL HARDCASES





TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATIONS



ADX-02

SERİSİ / SERIES

	UZUNLUK LENGTH		GENİŞLİK WIDTH		DERİNLİĞİ DEPTH		KAPAK DERİNLİĞİ COVER DEPTH		GÖVDE DERİNLİĞİ BODY DEPTH	
İÇ ÖLÇÜLER INTERIOR DIMENSIONS	243	9,56	188	7,4	105	4,13	30	1,18	75	2,95
DIŞ ÖLÇÜLER EXTERNAL DIMENSIONS	272	10,7	249	9,8	124	4,88				
BOŞ AĞIRLIK EMPTY WEIGHT	1,125 KG / 2,48 lb.									
HACİM CAPACITY	4,79 Lt. / US gal dry 1,26									
ÇALIŞMA SICAKLIĞI OPERATING TEMPERATURE	°C (min -30 / max.+65) / °F (min -22 / max.149)									

TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATIONS



ADX-03

SERİSİ / SERIES

	UZUNLUK LENGTH		GENİŞLİK WIDTH		DERİNLİĞİ DEPTH		KAPAK DERİNLİĞİ COVER DEPTH		GÖVDE DERİNLİĞİ BODY DEPTH	
İÇ ÖLÇÜLER INTERIOR DIMENSIONS	313	12,32	242	9,52	130	5,1	30	1,18	100	3,93
DIŞ ÖLÇÜLER EXTERNAL DIMENSIONS	345	13,58	302	11,88	150	5,9				
BOŞ AĞIRLIK EMPTY WEIGHT	1,72 KG / 3,79 lb.									
HACİM CAPACITY	9,85 Lt. / US gal dry 2,6									
ÇALIŞMA SICAKLIĞI OPERATING TEMPERATURE	°C (min -30 / max.+65) / °F (min -22 / max.149)									

TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATIONS



ADX-04

SERİSİ / SERIES

	UZUNLUK LENGTH		GENİŞLİK WIDTH		DERİNLİĞİ DEPTH		KAPAK DERİNLİĞİ COVER DEPTH		GÖVDE DERİNLİĞİ BODY DEPTH	
İÇ ÖLÇÜLER INTERIOR DIMENSIONS	390	15,35	305	12	140	5,51	40	1,57	100	3,93
DIŞ ÖLÇÜLER EXTERNAL DIMENSIONS	420	16,53	363	14,29	158	6,22				
BOŞ AĞIRLIK EMPTY WEIGHT	2,26 KG / 4,98 lb.									
HACİM CAPACITY	16,65 Lt. / US gal dry 4,39									
ÇALIŞMA SICAKLIĞI OPERATING TEMPERATURE	°C (min -30 / max.+65) / °F (min -22 / max.149)									

TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATIONS



SERİSİ / SERIES	UZUNLUK LENGTH		GENİŞLİK WIDTH		DERİNLİĞİ DEPTH		KAPAK DERİNLİĞİ COVER DEPTH		GÖVDE DERİNLİĞİ BODY DEPTH	
	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)
İÇ ÖLÇÜLER INTERIOR DIMENSIONS	390	15,35	305	12	190	7,48	40	1,57	150	5,9
DIŞ ÖLÇÜLER EXTERNAL DIMENSIONS	420	16,53	365	14,37	208	8,18				
BOŞ AĞIRLIK EMPTY WEIGHT	2,59 KG / 5,72 lb.									
HACİM CAPACITY	22,60 Lt. / US gal dry 5,97									
ÇALIŞMA SICAKLIĞI OPERATING TEMPERATURE	°C (min -30 / max.+65) / °F (min -22 / max.149)									

TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATIONS



SERİSİ / SERIES	UZUNLUK LENGTH		GENİŞLİK WIDTH		DERİNLİĞİ DEPTH		KAPAK DERİNLİĞİ COVER DEPTH		GÖVDE DERİNLİĞİ BODY DEPTH	
	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)
İÇ ÖLÇÜLER INTERIOR DIMENSIONS	460	18,1	330	13	130	5,1	50	1,96	80	3,15
DIŞ ÖLÇÜLER EXTERNAL DIMENSIONS	490	19,3	390	15,35	153	6,02				
BOŞ AĞIRLIK EMPTY WEIGHT	2,8 KG / 6,17 lb.									
HACİM CAPACITY	19,73 Lt. / US gal dry 5,21									
ÇALIŞMA SICAKLIĞI OPERATING TEMPERATURE	°C (min -30 / max.+65) / °F (min -22 / max.149)									

TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATIONS



SERİSİ / SERIES	UZUNLUK LENGTH		GENİŞLİK WIDTH		DERİNLİĞİ DEPTH		KAPAK DERİNLİĞİ COVER DEPTH		GÖVDE DERİNLİĞİ BODY DEPTH	
	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)
İÇ ÖLÇÜLER INTERIOR DIMENSIONS	460	18,1	330	13	170	6,7	50	1,96	120	4,72
DIŞ ÖLÇÜLER EXTERNAL DIMENSIONS	490	19,3	390	15,35	193	7,6				
BOŞ AĞIRLIK EMPTY WEIGHT	3,08 KG / 6,79 lb.									
HACİM CAPACITY	25,8 Lt. / US gal dry 6,81									
ÇALIŞMA SICAKLIĞI OPERATING TEMPERATURE	°C (min -30 / max.+65) / °F (min -22 / max.149)									

TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATIONS



SERİSİ / SERIES	UZUNLUK LENGTH		GENİŞLİK WIDTH		DERİNLİĞİ DEPTH		KAPAK DERİNLİĞİ COVER DEPTH		GÖVDE DERİNLİĞİ BODY DEPTH	
	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)
İÇ ÖLÇÜLER INTERIOR DIMENSIONS	525	20,6	350	13,8	200	7,87	50	1,96	150	5,9
DIŞ ÖLÇÜLER EXTERNAL DIMENSIONS	570	22,4	421	16,6	240	9,44				
BOŞ AĞIRLIK EMPTY WEIGHT	6,27 KG / 13,82 lb.									
HACİM CAPACITY	36,75 Lt. / US gal dry 9,71									
ÇALIŞMA SICAKLIĞI OPERATING TEMPERATURE	°C (min -30 / max.+65) / °F (min -22 / max.149)									

TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATIONS

SERİSİ / SERIES	UZUNLUK LENGTH		GENİŞLİK WIDTH		DERİNLİĞİ DEPTH		KAPAK DERİNLİĞİ COVER DEPTH		GÖVDE DERİNLİĞİ BODY DEPTH	
	(mm)	(inc)	(mm)	(inc)	(mm)	(inc)	(m)	(inc)	(mm)	(inc)
İÇ ÖLÇÜLER INTERIOR DIMENSIONS	525	20,6	350	13,8	275	10,8	m)	1,96	225	8,85
DIŞ ÖLÇÜLER EXTERNAL DIMENSIONS	570	22,4	421	16,6	315	12,4	50			
BOŞ AĞIRLIK EMPTY WEIGHT	6,82 KG / 15,03 lb.									
HACİM CAPACITY	50,53 Lt. / US gal dry 13,35									
ÇALIŞMA SICAKLIĞI OPERATING TEMPERATURE	°C (min -30 / max.+65) / °F (min -22 / max.149)									